

DECLARATION OF PERFORMANCE

According to CPR (EU) No.305/2011

Document No. 03-2026

1.	Unique identification code of the product-type	ESCO CS506EN and ESCO DS637EN
2.	Type, batch or serial number or any other element allowing identification of the construction product	Batch or serial number: See print on the product Brand: EnormPA
3.	Intended use/s of the construction product as foreseen by the manufacturer	Fire detection and fire alarm systems components of voice alarm systems - Loudspeakers Wall Mounted Speaker: DS637EN, 2,5-5W Trf 16 cm Type A IP21C Ceiling Mounted Speaker: CS506EN
4.	Name and address of the manufacturer	Mikafon Elektronik İnş.San.Ltd.Şti. Şair ziya paşa str, No:8 Beyoğlu/İstanbul (head office) Post code 34420 Keten str No:11 Çayırova/Kocaeli (manufacturing facility) Post code 41420 Phone: +90 212 244 51 77 (pbx) Fax: +90 212 244 51 75 Email: info@mikafon.com.tr
5.	Authorised representative	Not applicable
6.	System or systems of assessment and verification of constancy of performance (AVCP)	System-1
7.	Harmonised standard and notified body	Standard: EN 54-24:2008 Dedal Attestation & Certification Ltd, Notified body number 1922 Certificate No. 1922-CPR-2080
8.	Address of the notified body/ies	Bulgaria, 8000 Burgas, 54 Macedonia Str.

9. Declared Performance

Essential characteristics	Performance	Harmonised technical specification EN 54-24:2008
Performance parameters under fire conditions		
- Frequency response limits	Pass	4.2
- Reproducibility	Pass	5.2
- Rated impedance	Pass	5.3
- Horizontal and vertical coverage angles	Pass	5.4
- Maximum sound pressure level	Pass	5.5
Operational reliability		
- Durability	Pass	4.3
- Construction	Pass	4.4
- Marking and data	Pass	4.5
- Rated noise power (durability)	Pass	5.6
- Enclosure of the loudspeaker	Pass	5.18
Durability of operational reliability: temperature resistance		
- Dry heat (operational)	Pass	5.7

- Dry heat (endurance)	N/A	5.8
- Cold (operational)	Pass	5.9
<i>Durability of operational reliability: humidity resistance</i>		
- Damp heat, cyclic (operational)	Pass	5.10
- Damp heat, steady state (endurance)	Pass	5.11
- Damp heat, cyclic (endurance)	N/A	5.12
<i>Durability of operational reliability: corrosion resistance</i>		
- Sulphur dioxide (SO2) corrosion (endurance)	Pass	5.13
<i>Durability of operational reliability: impact and vibration resistance</i>		
- Shock (operational)	Pass	5.14
- Impact (operational)	Pass	5.15
- Vibration, sinusoidal (operational)	Pass	5.16
- Vibration, sinusoidal (endurance)	Pass	5.17

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued in accordance with regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by

Ercan Polat / General Manager

Location and date of issue: Çayirova / Kocaeli, 21.08.2026