

GO-SOUND 15AMW

Battery-Powered Portable 2-Way Active Speaker with Trolley and MP3/Bluetooth™ player

GO-SOUND family is now enhanced by a new batterypowered portable PA series with 12" and 15" woofers GO-SOUND 12AMW and 15AMW that, in addition to MP3 player, USB, SD-card, and Bluetooth™ connection of MULTIMEDIA version, integrates two VHF wireless microphones with handheld transmitters, an Echo effect for the two microphone inputs and the two wireless microphones, a useful 5-band graphic EQ and a handy trolley with wheels and telescopic handle on top. They are AC or battery operated; the latter with a duration of about 2.5 hours at maximum volume and full charge. Amplification, as well as for the previous GO-SOUND 12A and AM versions, is equipped with a Class-AB 800W (mains powered) peakpower module. The polypropylene enclosure is strong and lightweight, with metallic grille, 36mm standard pole mount hole, and acoustic foam to protect the woofer and give a pleasant look.













KEY FEATURES

Sturdy polypropylene enclosure yet compact and lightweight

800W Class-AB power amplifier (Peak power, mains powered)

15" woofer, 1" compression driver

MP3 player with USB, SD Card and Bluetooth™

Dual VHF Handheld Wireless Microphone

Echo Effect

Unbalanced Microphone/Line inputs

5-Band Graphic EQ

Rechargeable Battery with 2.5-hour battery life

36 mm standard pole mount

Trolley system with wheels and one telescopic handle on top + 2 side handles





MORE SPECIFICATIONS

Speaker Type	Portable 2-way active speaker with rechargeable battery
Frequency response	60Hz-19KHz
Max. SPL	114dB (Mains Powered)
Transducers	15" Woofer; 1" Compression Driver
Directivity (HxV)	90° x 40° - 60°
Horn Type	Asymmetric
Amplifier	400W* Program, 800W* Peak Class AB (*Mains Powered)
Controls	Mic1&2 level, Line level, Echo level, Bluetooth/MP3 level, Master level, Wireless Mics On, W. Mic1 level, W. Mic2 level
5-Band Graphic EQ	100Hz, 330Hz, 1KHz, 3,3KHz, 10KHz (+/- 12dB)
Connections	Mic 1&2 6.3mm TS Jack, Line In L&R RCA Jack, Line Out L&R RCA Jack
Indicators	Power, Clip, Wireless Mic On, RF Mic1, RF Mic2, Battery Charge
Media player	USB, SD-Card, Bluetooth™, 2x16 LCD Display
Media player controls	Stop, Play/Pause, Next track, Previous track, Mode
Mains Power	230VAC-50Hz
Fuse	T1A-250V
External Power (no charge function)	12Vcc
External Add. Fuse	T10A-250V
Rechargeable Battery	12V-7AH Lead Battery (TC12-7.0 type)
Battery Dimension (WxHxD)	151 x 100 (poles Included) x 65 mm
Housing material	Polypropylene
Grille	o.8mm, steel
Handles	2 on sides; 1 telescopic on top
Trolley	2 Wheels and 1 Telescopic Handle, 31 cm max. extension
Pole Mount	Standard D36 mm
Speaker Dimension (WxHxD)	440 x 703 x 370 mm
Packing Dimension (WxHxD)	485 × 745 × 400 mm
Net Weight	14.0 kg
Gross Weight	17.2 kg

