




LIVEMAKER X SET

1800W Peak Power 2.1 Portable Column PA System with DSP

LIVEMAKER X is the result of years of experience gathered by SOUNDSATION in Portable Sound systems, a segment where quality, versatility and value for money are absolutely essential. LIVEMAKER X system with its powerful 1800-watt (Peak) power amp delivers astounding performance for mobile applications especially for musicians and DJs. The system is equipped with a high-performance 10" subwoofer, two satellite speakers (6 x 2.75" Wide-band Speakers) and integrated mixer. In addition to the Bluetooth, the system integrates a DSP for Audio with 4 Presets and a 24Bit DSP FX with 16 genuine effects to add to the MIC inputs choosing the level for each channel. The enclosures (ABS for the satellites and Plywood for the subwoofer) are strong and lightweight and have a pleasant look.



KEY FEATURES

1 x Subwoofer with integrated mixer and 2 x Satellite Passive speakers

Class-D 2 x 600W (RMS) Amplifier

One 10" Woofer (Subwoofer) and 6 x 2.75" Wide-band Speakers (3 for each satellite speaker)

2 Microphones/Line Inputs with 3 Band Equalizer (Low/Middle/High frequencies)

Bluetooth

AUX Input with 1 Stereo RCA Line Input, 2 x JACK 1/4 Inputs and 1 x Mini Jack Stereo Input

Dual Band Equalizer on AUX Input

A DSP for Audio output with 4 presets and a 24Bit DSP FX with 16 genuine effects

25 mm hole for satellite speaker pole mounting

Sturdy, compact and lightweight cabinets (ABS for the satellites and Plywood for the subwoofer).

Speaker Stands and Bag included

MORE SPECIFICATIONS

System	Portable Column PA Speakers; Speaker Type: 2.1 Portable System
Satellite and Subwoofer Max. SPL(@1m)	121dB
Frequency Range	50Hz-20kHz; Satellite Frequency response: 250Hz-20kHz; Subwoofer Frequency response: 50Hz-250Hz
Satellite RMS / Peak Power Capacity	150W/450 W (each satellite speaker)
Sensitivity (1m/1W) Satellite/Subwoofer	98dB/95dB
Satellite Nominal impedance	8ohm
Satellite Input	1 x Speakon connector
Satellite HF driver	6 x 2.75" Wideband Speakers voice coil
Satellite Crossover frequency	250Hz, -12 dB/octave
Satellite HF protection	Short protection
Satellite Pole mount	Ø 25mm
Satellite Housing material	ABS
Satellite Dimensions (WxDxH)	(2x) 107x107x560mm; Satellite Net weight: (2x) 1.72kg
Subwoofer Inputs	2x XLR/6.3mm Jack Combo, Mini Jack Stereo input 3.5mm, RCA, 6.3 Jack L+R/Bluetooth
MIC, Line, RCA Input impedance	4.7 kΩ (MIC), 22 kΩ (LINE & RCA)
MIC/Line in Sensitivity	-50dB (MIC), -20dB (LINE)
Line in Sensitivity	-20dB
EQ Control	LOW Freq, +/-12dB; MID Freq, +/-11dB; HIGH Freq, +/-11dB
DSP	24Bit DSP for Audio Output with 4 presets and a 24Bit DSP FX with 16 genuine effects dedicated to CH1 and CH2
Bluetooth connection distance	30m
Subwoofer amplifier	300W RMS @ 4ohm; Satellites amplifier: 150W RMS @ 8ohm (for each satellite speaker)
LF driver	1 x10"Woofer 2.0" voice coil
Mains	110V~120V / 230V~240V
Fuse	110V~120V T10A / 230V~240V T5A
Pole Mount (subwoofer)	M20 thread
Subwoofer Dimensions (WxDxH)	325x520x383mm; Subwoofer Net weight: 15.9kg
Subwoofer Housing material	Plywood
Subwoofer Carton Size (WxDxH)	59,5x37,5x60,6cm; Satellite Stand Carton Size (WxDxH): 12,5x22,5x105,5cm
Stand Material	Steel; Stand Diameter: 25mm; Stand Height: 1.8m; Stand Carrying Bag: Included
Accessories	2x 3m Speakon-Speakon speaker cables, 1x 1.5m Schuko-IEC power cable, 1x Padded bag for speaker columns, 1x speaker stand set with